

PRESS RELEASE



FOR IMMEDIATE RELEASE

Ricoh Web Site: www.ricoh-usa.com

CONTACT: Linda Montefusco
Ricoh Americas Corporation
(973) 882-2172
Linda.Montefusco@ricoh-usa.com

Rebecca Maas
Peppercom
(212) 931-6126
rmaas@peppercom.com

RICOH LAUNCHES PRO 907EX/PRO 1107EX/PRO 1357EX DIGITAL IMAGING SYSTEMS

Series Upgrade Features Enhanced Speed, Productivity and Finishing

West Caldwell, N.J., July 21, 2009 – Ricoh Americas Corporation, the leading provider in digital office equipment, today launched the Ricoh Pro 907EX/Pro 1107EX and Pro 1357EX Digital Imaging Systems. These systems feature enhancements to the current Ricoh Pro 906EX/Pro 1106EX and Pro 1356EX series, which launched in May 2008, including advanced performance and improved finishing features. An extension of Ricoh's commitment to production printing, the series is designed to better meet the present needs of the demanding marketplace.

Built upon proven technology, the series exhibits high productivity, versatile finishing, and increased durability. The Ricoh Pro 907EX/Pro 1107EX/Pro 1357EX leads the market in print speed with 135 pages-per-minute (ppm), and offers faster performance due to its enhanced memory architecture, which includes a standard 512 MB RAM (upgradeable to 1.5 GB) and a 320 GM Hard Disk Drive. The series also provides its users expanded in-house capabilities, therefore limiting the need for outsourcing. By handling a wider variety of media sizes and stocks, as well as high-volume runs of large, multi-page documents the need to pause and re-load trays is greatly minimized.

Flexible finishing options give customers more variety of professionally-finished documents, without losing valuable production time. The Ricoh Pro 907EX/Pro 1107EX/Pro 1357EX can create perfect-bound books up to 400 pages (duplex) using its in-line Perfect Binder, and Ricoh's Ring Binder Unit can produce ready-to-distribute ring-bound booklets that are seamlessly punched and bound completely on-line. These features significantly reduce labor costs when printing bound books, passing on additional savings to customers.

Customers can expect reliable, un-interrupted operation in both the long-term, as well as during peak production. The Ricoh Pro 907EX/Pro 1107EX/Pro 1357EX identifies and corrects multiple-sheet feeding, with an innovative ultrasonic sensor that improves detection accuracy. The sensor ensures maximum uptime for high-volume copying, printing and scanning, and uses precise airflow to ensure fast, error-free media handling. The series is also equipped with enhanced Trained Customer Replaceable Units (TCRU's) which minimize downtime and don't require a service call.

"The production printing market is constantly changing and Ricoh strives to offer products and solutions that meet these demands and the needs of our customers," said Carl Joachim, vice president of Marketing, PPBG, Ricoh Americas Corporation. "By bringing this upgraded series to market, we're offering our customers the precision, speed and flexibility they need to succeed in an ever-increasing competitive landscape."

The Ricoh Pro 907EX/Pro 1107EX/Pro 1357EX systems are designed for simple operation by eliminating errors and performing administrative tasks remotely. Users can preview and approve thumbnails of scanned documents before final output or distribution via Scan-to-Email or Scan-to-Folder. With Web Image Monitor, a utility that allows users to check supply levels, change print queues and adjust settings, administrative tasks can be performed remotely, allowing for increased multitasking and decreased time spent at the system. The systems also feature the Super VGA Color Touch Panel Display, which provides convenient viewing of copy/scan options.

Security continues to be an essential tool with the upgraded series. Advanced security features allow customers to protect sensitive customer documents, and the system itself, by requiring identification confirmation of individuals prior to system access. Internal and external authentication, along with access restriction, control which features authorized users can employ. Users can prevent Denial of Service (DoS) attacks, reduce the risk of virus relay and defend against user name/password theft with the Network Protocol On/Off function. Protecting data from interception, analysis and tampering with encrypted transmission is supported by Secure Socket Layer (SSL) technology.

The Pro 907EX/Pro 1107EX/Pro 1357EX is available at a suggested retail price of \$40,000, \$51,000 and \$62,000, respectively.

To learn more about Ricoh's full line of products, please visit www.ricoh-usa.com.

About Ricoh Americas Corporation

Ricoh Americas Corporation, headquartered in West Caldwell, N.J., is a subsidiary of Ricoh Company Ltd., the 73-year-old leading supplier of office automation equipment and electronics, with fiscal year 2008 sales in excess of \$20 billion.

Ricoh Americas Corporation is a leading provider of document solutions. Ricoh's fully integrated hardware and software products help businesses share information efficiently and effectively by enabling customers to control the input, management and output of documents.

Ricoh Americas Corporation directly or through its network of authorized dealers markets and distributes products in North, Central and South America.

Information about Ricoh's complete range of products and services can be accessed on the World Wide Web at www.ricoh-usa.com.

#

All referenced product names are the trademarks of their respective companies.

Ricoh Pro 907EX/Pro 1107EX/Pro 1357EX

| | |
|--|--|
| General Specifications | |
| Warm-Up Time | Less than 360 seconds |
| Media Weights | 14 lb. – 80 lb. Bond 50 lb. – 80 lb. Cover 90 lb. – 110 lb. Index |
| Standard Media Capacity | 3,000 sheets Tray 1: 2 x 1,000-Sheet Tray Tray 2: 1 x 500-Sheet Tray Tray 3: 1 x 500-Sheet Tray |
| Power Requirements | 208 – 240V, 50/60 Hz, 20A (dedicated outlet) |
| Power Consumption (Engine/FIN/LCT) | Less than 3,500W Pro 1357EX: Less than 4,000W |
| Dimensions (WxDxH) | 34.3" x 33.9" x 58.2" (engine) |
| Weight | 672.4 lbs. (engine) |
| System Specifications | |
| Speed | Pro 907EX: 90 pages-per-minute (ppm) Pro 1107EX: 110 ppm Pro 1357EX: 135 ppm |
| First Copy | Pro 907EX: 3.5 seconds Pro 1107EX: 3.2 seconds Pro 1357EX: 3.0 seconds |
| Throughput Size | 5.5" x 8.5" to 13" x 19.2" |
| HDD Capacity | 320 GB (160 GB x 2) |
| Memory Capacity | 512 MB (standard) 1.5 GB (standard + Printer/Scanner option) |
| Reduction/Enlargement | 25% -- 400% (1% increments) |
| System Accessories | |
| Document Feeder | |
| Original Paper Weights | 11 – 34 lb. Bond (simplex) 14 – 28 lb. Bond (duplex) |
| RT5000 LT/LCT Large Capacity Tray | |
| Paper Sizes Supported | 5.5" x 8.5" to 8.5" x 11" |
| Paper Capacity | 1,000 sheets (Tray 4) 1,000 sheets (Tray 5) 2,550 sheets (Tray 6) |
| Paper Weights | 14 lb. Bond – 80 lb. Cover (Tray 4/5) |
| Dimensions (WxDxH) | 21.2" x 28.7" x 38.6" |
| SR5000 100-Sheet Finisher | |
| Paper Weights | 14 lb. Bond – 100 lb. Cover |
| Shift Tray | 3,000 sheets (8.5" x 11") 1,500 sheets (8.5" x 14"/11" x 17") |

| | |
|---------------------------------|--|
| | 1,000 sheets (13" x 19.2") |
| Proof Tray | 500 sheets (8.5" x 11") 250 sheets (8.5" x 14" or larger) |
| Staple Capacity | 100 sheets (based on 20 lb. Bond) |
| Dimensions (WxDxH) | 31.5" x 28.7" x 38.6" |
| C15010 Cover Interposer | |
| Paper Sizes Supported | 5.5" x 8.5" to 13" x 19.2" |
| Paper Capacity | 2 x 200 sheets |
| Paper Weights | 17 lb. Bond – 80 lb. Cover |
| Dimensions (WxDxH) | 27.9" x 28.7" x 50" |
| Weight | 99.2 lbs. |
| BY5000 Multi Bypass Tray | |
| Paper Capacity | 500 sheets (based 8.5" x 11") |
| Paper Sizes Supported | 5.5" x 8.5" to 12" x 18" (RT5030) 5.5" x 8.5" to 13" x 19.2" (RT5040) |
| PU5000 Punch Unit | |
| Punch Type | 2 or 3 holes (user-selectable) |
| Weights Punched | 16 lb. Bond – 90 lb. Index |
| Ring Binder RB5000 | |
| Paper Sizes Supported | 8.5" x 11" (LEF only) |
| Maximum Binding Capacity | 100 sheets/booklets |
| Rind Sizes Supported | 50-sheet/100-sheet |
| Capacity of Ring Bind | 2 – 100 sheets |
| Paper Weight Punched | 17 lb. Bond – 80 lb. Cover |
| Paper Weight Bound | 17 lb. Bond – 80 lb. Cover |
| Dimensions (WxDxH) | 34.2" x 28.7" x 38.5" |
| Power Requirements | 120V, 60 Hz |
| Perfect Binder GB5000 | |
| Maximum Booklet Capacity | 200 sheets (400 pages in duplex mode) |
| Paper Sizes Supported | Width 10.11" – 12.59", Length 7.16" – 9", 17 lb. Bond – 60 lb. Index (Body Pages); Width 10.11" – 13", Length 14.3" – 19.20", 24 – 40 lb. Bond – 100 lb. Cover (Cover Pages); Width 7.9" – 11.7", Length 5.5" – 8.5" (Booklet Size) |
| Dimensions (WxDxH) | 42.91" x 31.14" x 54.60" |
| Interposer Tray | Capacity: 2 x 200 sheets |
| Power Requirements | 220 – 240V, 50/60Hz |
| GBC StreamPunch III | |
| Punch Type | Customer-replaceable die sets |
| Paper Size Supported | 8.5" x 11", long edge feed (11" side only) |
| Systems Supported | Ricoh Pro 907EX/Pro 1107EX/Pro 1357EX |
| Dimensions (WxDxH) | 12" x 28.5" x 38.5" |
| SR5020 Booklet Finisher | |
| Media Size Supported | Up to 13" x 19.2" |

| | |
|-------------------------------|---|
| Media Weights | 14 lb. Bond – 80 lb. Cover (without Z-folding) 18 lb. – 28 lb. Bond (with Z-folding) |
| Stacking Capacity | Proof Tray: 250 sheets (letter or smaller) 50 sheets (8.5" x 14" or larger) Shift Tray: 2,500 sheets (8.5" x 11" LEF) 1,500 sheets (letter SEF, 11" x 17" SEF) |
| Staple Capacity | 100 sheets (8.5" x 11" – 13" x 19.2") 50 sheets (8.5" x 14" or 11" x 17") |
| Saddle Stitch | Media Size (8.5" x 11" – 13" x 19.2") Media Weight (18-24 lb. Bond) Staple Position: Center 2 Position Staple Capacity: 20 sheets (18-20 Bond), 15 sheets (20-24 lb. Bond) |
| Hole-Punching (optional) | 2 or 3 holes |
| Printer Specifications | |
| CPU | Intel Pentium M 1.4 GHz |
| Memory | 512 MB standard 1.5 GB (standard + Printer/Scanner Unit) |
| HDD Capacity | 320 GB (320 GB x 1) |
| Drivers / PDL | RPCS, PCL5e/6 Optional: Adobe® PostScript 3™, Genuine IPDS |
| Print Resolution | 1200 dpi (max.) |
| Fonts | PCL: TrueType: 45 Intellifonts, 13 International Fonts Optional: PS3: 136 Adobe Type 1 |
| Standard Connectivity | 100Base-TX/10Base-T Ethernet, USB 2.0 |
| Optional Connectivity | IEEE 1284, IEEE 802.11a/b/g Wireless LAN, Bluetooth, 1000Base-T |
| Network Protocol | TCP/IP, IPX/SPX, AppleTalk |
| Operating Systems | Windows 2000, XP, Vista, Server 2003, Server 2008 Mac OS 8.6 – 9.2.X (OS X Classic) Mac OS 10.1.X – 10.4.X Max OS 10.5.X |
| Utilities Supported | Web Image Monitor, Web SmartDeviceMonitor, SmartDeviceMonitor, Printer Utility for Mac, PDF Direct Printing (through DeskTopBinder), DeskTopBinder |
| Printer Options | IEEE 802.11a/b/g Wireless, Interface Gigabit Ethernet, Bluetooth |

| | |
|-------------------------------|--|
| | Interface |
| Scanner Specifications | |
| Scan Speed | 80 spm (black & white or color) |
| Optical Resolution | 100/150/200/300/400/600 dpi |
| TWAIN Resolution | 100 –1200 dpi (black & white or color) |
| File Formats | TIFF/JPEG/PDF and High Compression PDF |
| Scan-to-Email | |
| Requirement | SMTP Gateway and TCP/IP |
| E-mail Addresses | 2,000 addresses |
| Maximum Addresses/Send | 500 addresses |
| Address Support via LDAP | 100 addresses |
| Scan-to-Folder | |
| Protocol Support | SMB/FTP/NCP |
| Resolution | 100/150/200/300/400/600 dpi |
| Max. Client Folders Per Send | 50 |
| File Types Supported | Single Page TIFF/JPEG/PDF, Multi-Page TIFF/PDF, High Compression PDF |